

Cold water cage units

HD 9/50-4



Order no.: 1.367-151.0



Technical data

| | |
|----------------------------------|------------------|
| Operating pressure (bar/MPa) | max. 500/max. 50 |
| Water flow rate (l/h) | 900 |
| Max. water feed temperature (°C) | max. 60 |
| Pump type | - |
| Drive | - |
| Power rating (hp) | 15 |
| Electric starter | - |
| Weight (kg) | 190 |
| Dimensions (L x W x H) (mm) | 930x800x920 |

Accessories

Coupling

Double pipe union

For connecting and extending HP hoses. 2 x M 22 x 1,5 connections, brass with rubber protector

Order no. 4.403-002.0



Kaltwasser Cage Geräte

Order no. 6.415-915.0



High pressure hose DN 8 / 50Mpa / 20 m

Order no. 6.391-857.0



High pressure hose DN 8 / 50Mpa / 3 m

Order no. 6.391-856.0



Order no. 6.391-848.0



Cold water cage units

HD 9/50-4



Kaltwasser Cage Geräte

Order no. 6.391-847.0



Order no. 6.391-846.0



Order no. 5.765-166.0



Order no. 5.765-162.0



Order no. 5.765-159.0



Screw connector part

Order no. 5.401-325.0



Kaltwasser Cage Geräte

Order no. 4.760-677.0



Order no. 4.760-675.0



Jet pipe complete 60 Mpa

Order no. 4.760-653.0



Order no. 2.851-028.0



ABS protection against water shortage el

Order no. 2.641-922.0



Order no. 6.391-848.0



Cold water cage units

HD 9/50-4



Kaltwasser Cage Geräte

Order no. 5.765-164.0



Order no. 4.775-803.0



Order no. 4.760-679.0



Rotary coupling

Rotary coupling

Reliably prevents high-pressure hose twisting. Connection M 22 x 1.5 m.
protector

Order no. 4.401-076.0

